

NOYES® **C-Series Software Release Notes**

Changes made from version 2.0.8 to 2.0.9

- Added translations for French, German, and Italian languages

Changes made from version 1.4.56 to 2.0.8

- Improved "New Job" Creation
- Added power manager support for new battery

Changes made from version 1.3.3 to 1.4.56

- Added a New Job Creation utility
- Improved how operator information is stored and transferred to TRM
- Improved "Back" button function when viewing results
- Added the ability to use two USB flash drives at one time
- General Settings
 - Added "Formatting" option to allow users to define Numeric and Date formats
 - Changed option name "View Version Information" to "View System Information"
 - Improved "Distance Units" setting to be utilized throughout application
 - Improved the editing of "AM" and "PM" when setting "Time"
- Auto Test
 - Setting Reference
 - Text "Connect Clean MM jumpers..." is larger
 - Added new graphics that show reference setup jumpers
 - Added "Verify Test Jumpers" step to all jumper test methods
 - Improvements made to when Reference "Set..." and "Not Set" is displayed
 - Auto Test-Results Pages
 - Improved Fibers Under Test Loss Review - Page 2, results no longer presented as Normal and Reverse directions
 - Removed definition of icons page, formerly Page 3 – no longer required with new data presentation
 - Modified test result display page to be shown on pages 1, 2, or 5 depending on which page (1, 2 or 5) user was viewing for the last tested Save of the cable
 - Improved how a fiber pair is displayed when the test results of one of the fibers has been deleted
 - Added update of fiber lengths during "Re-Test"
 - Auto Test Settings
 - Improved Launch, Receive and Calibration Cord setup by setting maximum and minimum lengths in "Test Method Setup"
 - Added the ability to change and create connector types for "Fiber Under Test Connectors"
 - Improved "Auto-Test Rule Parameters" page view to fit on one page
 - Improved the functionality of User Rules and Applications
 - Improved distance units settings to follow changes in the Main unit
 - Saving Tests
 - Improved the time it takes to save test results
 - Improved the save function to eliminate error messages when saving results of higher fiber pair counts
 - Message

continued on next page ->

NOYES**C-Series Software Release Notes**

- Edit message feature improved
- "Msg" button change to be consistent for when the unit is set as Main or Remote
- Added the ability to use a question mark when sending a message
- OPM
 - Improved Wave ID function by not allowing wavelengths to be changed when Wave ID is detected
 - Improved the way the measurement units display after changed
 - Changed the OPM icon
 - Improved "Save" functionality
- OTDR
 - Improved the adjustment speed of LSA lines
 - Changed how GIR and Backscatter display and where they can be adjusted
 - Improved soft key function for "Event Settings"
 - Improved "OTDR Located At" function in "Job Settings"
 - Improved "Zoom Adjust" functionality during testing
 - Improved "Re-Calc" function to add the adjustment of the Launch and Receive cables
 - Improved fiber number displayed while performing a test
 - Improved the auto selection of Range and Pulse Width to be consistent whether in "Full Auto" or in "Expert" with Auto or Auto Once selected