

## Indoor/Outdoor Multi-unit Riser Tight Buffered Cable

AFL now offers high fiber count Indoor/Outdoor Riser Cables. Waterblocked 12-fiber sub-units are helically stranded to provide sub-unitized cables ranging from 24 to 72 fiber counts. These cables are OFNR listed for indoor applications. Both the sub-unit jackets and outer sheath contain a UV stabilizer and anti-fungus protection for use in outdoor applications. Sub-units contain a water-swellable aramid and 12 tight buffered fibers.


### Features

- Available with 24 to 72 fibers
- 12-fiber water-blocked sub-units
- Moisture-resistant, fungus-resistant and UV-resistant sub-unit jackets and outer sheath

### Applications

- ONFR inside plant and outside plant environments

### Cable Components



### Fiber Specifications

CORE SIZE/FIBER TYPE	ISO/IEC	MAXIMUM ATTENUATION (DB/KM)			OVERFILL LAUNCH MIN. BANDWIDTH (MHZ•KM)		EMB <sub>c</sub> (MHZ•KM)	GIGABIT ETHERNET MIN. LINK DISTANCE (METERS)		10 GIGABIT ETHERNET MIN. LINK DISTANCE (METERS)	
		850 NM	1300 NM	1550 NM	850 NM	1300 NM		850 NM	1300 NM	850 NM	1300 NM
(6) 62.5 Giga-Link™ 300	OM1	3.5	1.2	N/A	200	600	N/A	300	550	32	—
(5) 50 Giga-Link™ 600	OM2	3.5	1.5	N/A	500	500	N/A	600	600	82	—
(L) 50 Laser-Link 300	OM3	3	1.2	N/A	1,500	500	2,000	1,000	550	300	—
(C) 50 Laser-Link 550	OM4	3	1.2	N/A	3,500	500	4,700	1,040	550	550	—
(W) AFL Wideband Multimode	OM5	3	1.2	N/A	3,500	500	4,700	1,040	550	550	—
(9) Single-mode (ITU G.652.D/G.657.A1)	OS2	N/A	0.5	0.5	N/A	N/A	N/A	N/A	5,000	N/A	10,000



## Indoor/Outdoor Multi-unit Riser Tight Buffered Cable

### Mechanical Data

CABLE TYPE	AFL NO.	FIBER COUNT	NOMINAL DIAMETER	WEIGHT	TENSION		BENDING RADIUS	
	RISER		INCHES (MM)	LBS/1000 FT (KG/KM)	LBS (N)		INCHES (CM)	
			INSTALLATION	LONG TERM	INSTALLATION	LONG TERM		
Indoor/Outdoor Tight Buffered Cable	KR024★611##1	24	0.67 (16.9)	169 (252)	300 (1320)	90 (396)	10.0 (25.3)	6.7 (16.9)
	KR036★611##1	36	0.67 (16.9)	178 (265)	300 (1320)	90 (396)	10.0 (25.3)	6.7 (16.9)
	KR048★611##1	48	0.67 (16.9)	187 (278)	300 (1320)	90 (396)	10.0 (25.3)	6.7 (16.9)
	KR060★611##1	60	0.76 (19.2)	197 (293)	300 (1320)	90 (396)	11.3 (28.8)	7.6 (19.2)
	KR072★611##1	72	0.81 (20.7)	233 (346)	300 (1320)	90 (396)	12.2 (31.0)	8.1 (20.7)

★ Fiber Types – Replace asterisk (★) in AFL number with number in the Fiber Specifications table on previous page.

# Outer Jacket Color – Replace hashtag (#) in AFL number with number in the Cable Jacket Color table below.

### Cable Jacket Color Options

1 - Blue	8 - Black
2 - Orange	9 - Yellow
3 - Green	A - Violet
4 - Brown	B - Rose
5 - Slate	C - Aqua
6 - White	K - Erika Violet (RAL 4003)
7 - Red	

### Qualifications

GOVERNING BODY	STANDARD CODE	COMPONENT
Telcordia	GR-20-CORE GR-409-CORE	Water-Blocked Cabled Buffer Tube Core Sub-units
EIA/TIA	598-A	Sub-units
ICEA	S-104-696	Sub-units
RoHS	2002/95/EC	Cable

### Temperature Specifications

TEMPERATURE RANGE	
Installation	-20°C to +75°C
Operation	-40°C to +75°C
Storage	-40°C to +75°C

Contact AFL for further details.