



CG-1000XL

## CableGuard 1000XL Coax Demarcation Enclosures

The CableGuard CG-1000XL Coax Demarcation Enclosure provides a secure compartment for terminating coax, and mounting splitters and/or a ground blocks. Constructed of a weather-resistant/high impact thermoplastic alloy, the hinged cover design allows easy access, while the self-sealing individual entrance ports prevent water and insects from entering. The organized mounting arrangements not only create a standardized method for high quality drop installations, but also allow future expandability.

### Features

- Weather-resistant/high impact thermoplastic alloy
- Self-latching, hinged cover design allows easy access without loose parts
- Organized internal mounting bosses create a standardized mounting arrangement and allow for proper bend radius of coax cable up to RG-6
- Upgradeable/separate secure subscriber compartment
- Upgradeable telephony demarcation
- Self-sealing individual entrance ports prevent water and insects from entering
- Optional custom logo
- Optional secure ground block protection

### Specifications

PARAMETER	VALUES
Dielectric Strength	Minimum 2500 Vrms for 1 minute
Torque (mounting bosses)	20 in./lbs.
High Temperature Storage/Mold Stress °F (°C)	14 days at 159 (70.55)
Temperature Cycling with Humidity °F (°C)	150 day cycling from 40 to 140 (4.44 to 60) with 95% RH
Impact Test °F (°C)	-40 (-40), 5 ft./lbs. on all external surfaces
Drop Test °F (°C)	-40 (-40), 5 ft. (152.4 cm) onto concrete surface 4 times
Rain	24 hours at 10 psi
UV Resistance (Days Exposed)	60 per ASTM-G26-84
Salt Fog (Days Exposed)	60 per ASTM-BLL7-90
Flammability	UL94-5V
Chemical Resistance	30 Days at 100°F and 95% RH, Resists chipping and/or cracking when subject to: house paint, wasp spray, sulfuric acid, kerosene and sodium hydroxide
Material	UL® listed flame retardant thermoplastic alloy
Dimensions (H x W x D) in. (cm)	9.00 x 9.00 x 5.25 (22.80 x 22.80 x 13.34)
Cable Entrances in. (cm) diameter - Output	5 x 0.625 (1.5)
Cable Entrances in. (cm) diameter - Input	1 x 0.625 (1.5), 1 x 0.250 (0.6) (ground wire)
Covers	Molded in snap finger and 3/8" hex head fastener or F term

### Ordering Information

MODEL NO.	AFL NO.
CG-1000 XL, F Terminator Security (not included)	DM000336