

# AFL HiTemp Filler Compound

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Date of issue: 03/22/2017

Revision date: 03/22/2017

Version: 1.0

### SECTION 1: Identification

#### 1.1. Identification

Product name : AFL HiTemp Filler Compound

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Corrosion inhibitor

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

AFL TELECOMMUNICATIONS LLC  
170 RIDGEVIEW CIRCLE  
DUNCAN, SC 29334 USA  
T 864-433-0333  
WWW.AFLGLOBAL.COM

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC: 800-424-9300

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

##### GHS classification

Skin Sens. 1  
Carc. 2  
STOT RE 1

#### 2.2. Label elements

##### GHS labelling

Hazard pictograms (GHS) :



GHS07



GHS08

Signal word (GHS) :

Danger

Hazard statements (GHS) :

May cause an allergic skin reaction. Suspected of causing cancer. Causes damage to organs through prolonged or repeated exposure

Precautionary statements (GHS) :

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If on skin: Wash with plenty of water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Store locked up. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity

Not applicable

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%
Aluminum oxide (Al <sub>2</sub> O <sub>3</sub> )	(CAS-No.) 1344-28-1	40.00
Nickel	(CAS-No.) 7440-02-0	10.00
Aluminum	(CAS-No.) 7429-90-5	10.00

# AFL HiTemp Filler Compound

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures after inhalation : Not a normal route of exposure. If symptoms develop, remove to fresh air. Get medical attention if condition worsens.
- First-aid measures after skin contact : IF ON SKIN: Wash with plenty of Water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. This compound contains abrasive particles. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after inhalation : Not a normal route of exposure.
- Symptoms/effects after skin contact : May cause skin irritation. Symptoms may include redness, drying, and cracking of the skin. May cause an allergic skin reaction.
- Symptoms/effects after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- Symptoms/effects after ingestion : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

### SECTION 5: Fire-fighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Dry chemical. Foam. Carbon dioxide.
- Unsuitable extinguishing media : Do not use water jet.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon. Silicon dioxide. Formaldehyde.
- Reactivity : No dangerous reactions known under normal conditions of use.

#### 5.3. Advice for firefighters

- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

##### 6.1.1. For non-emergency personnel

No additional information available

##### 6.1.2. For emergency responders

No additional information available

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters.

#### 6.3. Methods and material for containment and cleaning up

- For containment : Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
- Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Spilled material may present a slipping hazard.

#### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

# AFL HiTemp Filler Compound

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Avoid contact with skin and eyes. Do not swallow. Do not breathe dust, fume, gas, mist, spray, vapours. Handle and open container with care. When using do not eat, drink or smoke.
- Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep out of the reach of children. Keep container tightly closed. Store locked up.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Aluminum oxide (Al <sub>2</sub> O <sub>3</sub> ) (1344-28-1)		
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable fraction)
Nickel (7440-02-0)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	1.5 mg/m <sup>3</sup> (inhalable particulate matter)
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup>
IDLH	US IDLH (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	0.015 mg/m <sup>3</sup>
Aluminum (7429-90-5)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup> (respirable particulate matter)
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable fraction)
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable dust)

#### 8.2. Exposure controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Hand protection : Wear suitable gloves resistant to chemical penetration.
- Eye protection : Safety glasses or goggles are recommended when using product.
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : None necessary under normal conditions of use. In case of insufficient ventilation, wear suitable respiratory equipment.
- Environmental exposure controls : Avoid release to the environment.
- Other information : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

- Physical state : Solid
- Appearance : Paste / thick grease
- Colour : Milky white
- Odour : Odourless
- Odour threshold : No data available
- pH : No data available
- Melting point : No data available
- Freezing point : No data available
- Boiling point : No data available
- Flash point : > 260 °C (>500 °F)
- Relative evaporation rate (butylacetate=1) : No data available
- Flammability (solid, gas) : Not flammable
- Vapour pressure : No data available
- Relative vapour density at 20 °C : No data available

# AFL HiTemp Filler Compound

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Relative density	: 2.3
Solubility	: Negligible
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Methylphenylpolysiloxanes can generate formaldehyde when heated to >149 °C (300 °F).

### 10.4. Conditions to avoid

Heat. Incompatible materials.

### 10.5. Incompatible materials

Strong acids. Strong alkalis. Oxidizing materials.

### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. Silicon dioxide. Formaldehyde.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified.
Acute toxicity (dermal)	: Not classified.
Acute toxicity (inhalation)	: Not classified.

#### Aluminum oxide (Al<sub>2</sub>O<sub>3</sub>) (1344-28-1)

LD50 oral rat	> 5000 mg/kg
---------------	--------------

#### Nickel (7440-02-0)

LD50 oral rat	> 9000 mg/kg
---------------	--------------

Skin corrosion/irritation	: Not classified.
Serious eye damage/irritation	: Not classified.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Suspected of causing cancer.

#### Nickel (7440-02-0)

IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity	: Not classified.
STOT-single exposure	: Not classified.
STOT-repeated exposure	: Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified.

# AFL HiTemp Filler Compound

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Symptoms/effects after inhalation	: Not a normal route of exposure.
Symptoms/effects after skin contact	: May cause skin irritation. Symptoms may include redness, drying, and cracking of the skin. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Nickel (7440-02-0)	
LC50 fish 1	> 100 mg/l (Exposure time: 96 h - Species: Brachydanio rerio)
EC50 Daphnia 1	> 100 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	1.3 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi-static])
EC50 Daphnia 2	1 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

#### 12.2. Persistence and degradability

AFL HiTemp Filler Compound	
Persistence and degradability	Not established.

#### 12.3. Bioaccumulative potential

AFL HiTemp Filler Compound	
Bioaccumulative potential	Not established.

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

Effect on the global warming : No known effects from this product.  
Other information : No other effects known.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

### SECTION 14: Transport information

#### Department of Transportation (DOT) and Transportation of Dangerous Goods (TDG)

In accordance with DOT/TDG

Not regulated

### SECTION 15: Regulatory information

#### 15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

#### 15.2. International regulations

No additional information available

#### 15.3. US State regulations

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer, developmental and/or reproductive harm

# AFL HiTemp Filler Compound

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### SECTION 16: Other information

Revision date : 03/22/2017  
Other information : None.  
Prepared by : Nexreg Compliance Inc.  
[www.Nexreg.com](http://www.Nexreg.com)



SDS HazCom 2012 - WHMIS 2015 (NexReg)

*Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.*