

Quick Reference Guide for Standard Compression Accessories for AAC and ACAR Conductors

Code Word	Conductor			Compression Accessories Catalog Number						
	Size		Diameter in	Dead End Assembly	Dead End Body Single Tongue	Steel Eye	Adjustable Clevis Assembly	15° Terminal	Compression Joint	Repair Sleeve
	Kcmil	Strand								
Akron	30.58	—	0.198	—	—	—	—	—	7506.250	—
Alton	48.69	—	0.250	—	—	—	—	—	7506.298	—
Ames	77.47	—	0.316	—	—	—	—	—	7509.375	—
Azuza	123.3	—	0.398	—	—	—	—	—	7511.453	5274
—	155.4	4/3	0.447	E33703	7612.484	9000	—	5112.484	—	5274
Anaheim	155.4	7	0.447	E33703	7612.484	9000	—	5112.484	7512.484	5274
—	195.7	4/3	0.502	E33704	7613.542	9000	—	5113.542	—	5275
Amherst	195.7	7	0.502	E33704	7613.542	9000	—	5113.542	7513.542	5275
—	246.9	4/3	0.563	E33705	7613.625	9000	—	5113.625	—	5275
Alliance	246.9	7	0.563	E33705	7613.625	9000	—	5113.625	7513.625	5275
Butte	312.8	19	0.642	E33707	7614.719	9100	—	5114.719	7514.719	5276
—	355.1	—	0.684	—	—	—	—	—	7514.719	5276
Canton	394.5	19	0.721	E33708	7624.781	9200	C43408	5124.781	7524.781	5220.3
—	419.6	—	0.743	—	—	—	—	—	7524.781	5220.3
Cairo	465.4	19	0.783	E33709	7624.875C	9200	C43409	5124.875	7524.875	5220.3
—	503.6	15/4	0.814	E33709	7624.875C	9200	C43409	5124.875	7524.875	5220.3
Darien	559.5	19	0.858	E33710	7627.906	9300	C43410	5127.906	7527.906	5224.3
—	561.1	—	0.862	—	—	—	—	—	7527.906	5224.3
—	587.2	—	0.879	—	—	—	—	—	7527.938	5224.3
—	634.9	12/7	0.914	E33712	7627.100	9200	C43412	5127.100	—	5224.3
—	649.5	18/19	0.928	E33716	7672.100C	9300	C43416	5127.100	—	5224.3
—	649.5	24/13	0.928	E33716	7672.100C	9300	C43416	5127.100	—	5224.3
—	649.5	30/7	0.928	E33716	7672.100C	9300	C43416	5127.100	—	5224.3
Elgin	652.4	19	0.927	E33713	7627.109	9300	C43413	5130.109	7530.109	5224.3
—	657.3	15/4	0.930	E33712	7630.100	9200	C43412	5127.100	—	5224.3
Flint	740.8	37	0.991	E33713	7630.109	9300	—	5130.109	7530.109	5227.3
—	751.4	—	0.609	—	—	—	—	—	7513.688	5276
—	853.7	18/19	1.063	E33717	7630.116	9300	C43417	5130.116	—	5230.3
—	853.7	24/13	1.063	E33717	7630.116	9300	C43417	5130.116	—	5230.3
—	853.7	30/7	1.063	E33717	7634.116	9300	C43417	5130.116	—	5230.3
Greeley	927.2	37	1.108	E33714	7634.122	9300	—	5134.122	7534.122	5230.3
—	927.2	18/19	1.108	E33714	7634.122	9300	C43414	5134.122	—	5230.3
—	927.2	24/13	1.108	E33714	7634.122	9300	C43414	5134.122	—	5230.3
—	927.2	30/7	1.108	E33714	7634.122	9300	C43414	5134.122	—	5230.3
—	1024.5	18/19	1.165	E33714	7634.122	9300	C43414	5134.122	—	5230.3
—	1024.5	24/13	1.165	E33714	7634.122	9300	C43414	5134.122	—	5230.3
—	1024.5	30/7	1.165	E33714	7634.122	9300	C43414	5134.122	—	5230.3
—	1080.6	18/19	1.196	E33716	7634.128	9400	C43415	5134.128	—	5230.3

Quick Reference Guide for Standard Compression Accessories for AAC and ACAR Conductors (cont.)

Code Word	Conductor			Compression Accessories Catalog Number						
	Size		Diameter in	Dead End Assembly	Dead End Body Single Tongue	Steel Eye	Adjustable Clevis Assembly	15° Terminal	Compression Joint	Repair Sleeve
	Kcmil	Strand								
—	1080.6	24/13	1.196	E33716	7634.128	9400	C43415	5134.128	—	5230.3
—	1080.6	30/7	1.196	E33716	7634.128	9400	C43415	5134.128	—	5230.3
—	1127.0	42/19	1.222	E33723	7638.138	E9500	—	5138.138	—	5234.3
—	1172.3	18/19	1.246	E33715	7634.128	9400	C43415	5134.128	—	5234.3
—	1172.3	24/13	1.246	E33715	7634.128	9400	C43415	5134.128	—	5234.3
—	1180.6	24/13	1.212	E33715	7634.128	9400	C43415	5134.128	—	5234.3
—	1534.0	42/19	1.427	E33718	7638.150	E9600	C43418	5138.150	—	5238.3
—	1534.0	54/7	1.427	E33718	7638.150	E9600	C43418	5138.150	—	5238.3
—	1691.0	—	1.498	E33722	7644.159	E9700	—	5144.159	—	5240.3
—	1700.0	42/19	1.502	E33719	7640.162	E9600	C43419	5140.162	—	5240.3
—	1700.0	54/7	1.502	E33719	7640.162	E9600	C43419	5140.162	—	5240.3
—	2303.5	54/37	1.750	E33720	7648.184	E9800	—	5148.184	—	5244.3
—	2303.5	63/28	1.750	E33720	7648.184	E9800	—	5148.184	—	5244.3
—	2338.0	42/19	1.762	E33720	7648.184	E9800	—	5148.184	—	5244.3

QRG—STANDARD
COMPRESSION