

Hydraulic Hoses



The 1/4" (0.635 cm) non-conductive, orange hose is made of an insulated, synthetic material. It allows a high flow rate for faster ram movement. Hoses are available with or without couplers for operating pressures of 10,000 PSI with a 4 to 1 burst ratio. Hoses are pre-filled with oil and pressure tested. The hoses are 3/8" NPT male thread on both ends and quick disconnects are 3/8" NPT female.

Ordering

AFL NO.	DESCRIPTION
6HOSEM/M	6 Foot Hose with Male/male Couplers (1.83 Meters)
10HOSEM/M	10 Foot Hose with Male/male Couplers (3.04 Meters)
15HOSEM/M	15 Foot Hose with Male/male Couplers (4.37 Meters)
25HOSEM/M	25 Foot Hose with Male/male Couplers (7.62 Meters)
6HOSEM/F	6 Foot Hose with Male/female Couplers (1.83 Meters)
10HOSEM/F	10 Foot Hose with Male/female Couplers (3.04 Meters)
15HOSEM/F	15 Foot Hose with Male/female Couplers (4.37 Meters)
25HOSEM/F	25 Foot Hose with Male/female Couplers (7.62 Meters)

WARNING: Hoses connecting hydraulic equipment should not extend straight upward more than 25 feet (7.6 meters).

Metal Carrying Cases



Features

- Sheet steel fabrication
- Enamel finish
- Piano hinged lid with latch
- Carrying handle

Ordering

AFL NO.	TOOL	LENGTH	WIDTH	HEIGHT
3-8744	14HTR	7.50 in (19.50 cm)	15.50 in (39.37 cm)	4.00 in (10.16 cm)
3-8739	60AGSC	8.87 in (22.53 cm)	11.37 in (28.88 cm)	19.12 in (48.56 cm)
3-8739	60AFTGSC	8.87 in (22.53 cm)	11.37 in (28.88 cm)	19.12 in (48.56 cm)

WARNING: Do not operate any compression tool without dies.