


Connector Kits for Opti-Guard Splice Enclosures—Black Jacket Cable

Connector Kit: All-Dielectric Self-Supporting Fiber Optic Cable



All-Dielectric Self-Supporting Connector Kit

BCK

Black Jacket Cable
Connector Kit

XXX/XXX


Range Code in
Decimal Inches
(see Table 1 below)

F

Blank = No Additional Connector
Assembly Required
F = 1" Flex Conduit Connector Required

Ordering Example: For 0.528" diameter ADSS, the AFL number is BCK522/537.

Connector Kit: Loose Tube Fiber Optic Cable



Armored Loose Tube Connector Kit

BCK

Black Jacket Cable
Connector Kit

XXX/XXX

Range Code in
Decimal Inches
(see Table 1 below)

B

Options
Blank = No Additional Connector
Assembly Required
F = 1" Flexible Conduit Connector Required
A = Armor Ground Assembly Required
B = Armor Ground Assembly and 1" Flexible
Conduit Connector Required

Ordering Example: For 0.510" armored loose tube (duct) cable with flexible conduit and armor ground connections, the AFL number is BCK507/521B.

Table 1

RANGE CODE	CABLE DIAMETER RANGE	
	MIN.	MAX.
225/240	.225	.240
241/255	.241	.255
256/271	.256	.271
272/286	.272	.286
287/302	.287	.302
303/318	.303	.318
319/333	.319	.333
334/349	.334	.349
350/365	.350	.365
366/380	.366	.380
381/396	.381	.396
397/412	.397	.412
413/427	.413	.427
428/443	.428	.443
444/459	.444	.459
460/474	.460	.474
475/490	.475	.490

RANGE CODE	CABLE DIAMETER RANGE	
	MIN.	MAX.
491/506	.491	.506
507/521	.507	.521
522/537	.522	.537
538/553	.538	.553
554/568	.554	.568
569/583	.569	.583
584/599	.584	.599
600/615	.600	.615
616/630	.616	.630
631/646	.631	.646
647/662	.647	.662
663/677	.663	.677
678/693	.678	.693
694/708	.694	.708
709/727	.709	.727
728/740	.728	.740