



## TYPE SWAS-N-AA Swage Split Cable Spacer with NEMA Pad

### Material

Aluminum Alloy



CABLE SPACERS

*continued*  
→

## TYPE SWAS-N-AA

### Swage Split Cable Spacer with NEMA Pad

#### Ordering Information

AFL NO.	CABLE RANGE		DIMENSIONS IN INCHES		DIE SIZE
	AAC	ACSR	A	B	
SWAS1613-8-4N4-AA	2/0	1/0	9.00	8.00	45TD16
SWAS1625-8-4N4-AA	250	4/0	9.00	8.00	45TD16
SWAS2026-8-4N4-AA	266.8	266.8 (18/1)	9.00	8.00	45TD20
SWAS2030-8-4N4-AA	300	266.8 (26/7)	9.00	8.00	45TD20
SWAS2035-8-4N4-AA	336.4, 350	300 (26/7), 336.4 (18/1)	9.00	8.00	45TD20
SWAS2039-8-4N4-AA	397.5	336.4 (26/7), 336.4 (30/7), 397.5 (18/1)	9.00	8.00	45TD20
SWAS2445-8-4N4-AA	450	397.5 (24/7), 397.5 (26/7)	9.13	8.00	45TD24
SWAS2447-8-4N4-AA	477	397.5 (30/7)	9.13	8.00	45TD24
SWAS2450-8-4N4-AA	500	477 (18/1)	9.13	8.00	45TD24
SWAS2455-8-4N4-AA	556.5	477 (24/7), 477 (26/7)	9.13	8.00	45TD24
SWAS2860-8-4N4-AA	600	477 (30/7), 556.5 (18/1)	10.00	8.00	45TD28
SWAS2863-8-4N4-AA	636	556.5 (24/7), 556.5 (26/7)	10.00	8.00	45TD28
SWAS2871-8-4N4-AA	700, 715.5	556.5 (30/7), 605 (24/7), 605 (26/7), 636 (18/1), 636 (36/1)	10.00	8.00	45TD28
SWAS3075-8-4N4-AA	750	605 (30/7), 605 (30/19), 636 (24/7), 636 (26/7)	10.00	8.00	45TD30
SWAS3079-8-4N4-AA	795	636 (30/7), 636 (30/19), 666.6 (24/7), 666.6 (26/7), 715.5 (24/7), 715.5 (54/7), 795 (36/1)	10.00	8.00	45TD30
SWAS3087-8-4N4-AA	874.5	715.5 (26/7), 715.5 (30/19), 795 (45/7)	10.00	8.00	45TD30
SWAS3290-8-4N4-AA	900	795 (24/7), 795 (54/7), 795 (26/7)	10.00	8.00	45TD32
SWAS3295-8-4N4-AA	954	795 (30/19), 900 (45/7)	10.00	8.00	45TD32
SWAS32100-8-4N4-AA	1000	874.5 (54/7), 900 (54/7), 954 (45/7)	8.00	8.00	45TD32
SWAS32103-8-4N4-AA	1033.5	954 (54/7)	10.00	8.00	45TD32
SWAS32111-8-4N4-AA	1113	1033.5 (45/7), 1033.5 (54/7)	10.00	8.00	45TD32
SWAS36119-8-4N4-AA	1192.5	1113 (45/7)	10.50	8.00	45TD36
SWAS36127-8-4N4-AA	1272	1113 (54/19), 1192.5 (45/7)	10.50	8.00	45TD36
SWAS36135-8-4N4-AA	1351.5	1192.5 (54/19), 1272 (45/7)	8.00	8.00	45TD36
SWAS36143-8-4N4-AA	1431	1272 (54/19), 1351.5 (45/7)	10.50	8.00	45TD36
SWAS36151-8-4N4-AA	1510.5	1351.5 (54/19), 1431 (45/7)	10.50	8.00	45TD36
SWAS36159-8-4N4-AA	1590	1431 (54/19), 1510.5 (45/7)	10.50	8.00	45TD36
SWAS36175-8-4N4-AA	1750	1510.5 (54/19), 1590 (45/7)	10.50	8.00	45TD36
SWAS36180-8-4N4-AA	1800	1590 (54/19)	10.50	8.00	45TD36
SWAS44200-8-4N4-AA	2000	1780 (84/19)	11.50	8.00	65TD44
SWAS44230-8-4N4-AA	2250	2156 (84/19), 2167 (72/7)	11.50	8.00	65TD44
SWAS44250-8-4N4-AA	2500	2312 (76/19)	11.50	8.00	65TD44