


Gel-Free Non-Armored OSP Loose Tube (LE Series Gel-Free SJ)

AFL LE-Series Gel-Free Single Jacket fiber optic cables are designed for outside plant applications and intended for use in communication network connects requiring cable to be installed within duct systems or lashed to aerial messenger wire structures. The product line incorporates the latest dry water-absorption technology within the fiber-containing buffer tubes which results in user-friendly handling of fibers during routing and termination within the slice enclosures.

Cable Components



Features

- Gel-free buffer tubes reduce fiber prep termination time
- SZ-stranded cable core for easy mid-span access of fibers
- UV-stabilized outer jacket for long-term performance in aerial applications
- 6 to 288 fibers allow for specific cable choices for multiple applications
- Standards compliance:
 - ANSI/ICEA S-87-640
 - Telcordia GR-20
 - RDUP PE-90

Temperature Specifications

TEMPERATURE RANGE	
INSTALLATION	-30°C to +70°C
OPERATING	-40°C to +70°C
STORAGE	-40°C to +75°C



**Rodent-deterrent Jacket
Option Available**

Typical Lengths

MAXIMUM LENGTHS*				
FIBER COUNT	SINGLE-MODE		MULTIMODE	
	FEET	METERS	FEET	METERS
6 - 60	22,900	7,000	22,900	7,000
72 - 96	22,900	7,000	22,900	7,000
108 - 120	22,900	7,000	22,900	7,000
132 - 144	22,900	7,000	22,900	7,000
146 - 216	22,900	7,000	22,900	7,000
218 - 288	16,400	5,000	16,400	5,000
290 - 432	14,100	4,300	14,000	4,300
434 - 576	10,800	3,300	11,000	3,300

* Longer lengths may be available upon request.

Fiber Specifications

FIBER TYPE	MAXIMUM ATTENUATION (DB/KM)				OVERFILL LAUNCH MIN. BANDWIDTH (MHZ•KM)		GIGABIT ETHERNET MIN. LINK DISTANCE (METERS)	
	850 NM	1300 NM	1310 NM	1550 NM	850 NM	1300 NM	850 NM	1300 NM
(6) 62.5/125 GIGA-Link™ 300	3.5	1.2	N/A	N/A	200	600	300	550
(5) 50/125 GIGA-Link™ 600	2.9	0.9	N/A	N/A	500	500	600	600
(L) 50/125 Laser-Link™ 300	2.9	0.9	N/A	N/A	1500	500	900	550
(9) Single-mode	N/A	N/A	0.35	0.25	N/A	N/A	N/A	5000
(Q) Non-zero Dispersion-shifted Single-mode	N/A	N/A	N/A	0.25	N/A	N/A	N/A	N/A
(K) AFL G.657.A1 Single-mode	N/A	N/A	0.35	0.25	N/A	N/A	N/A	5000

Gigabit Ethernet Minimum Link Distances are based on "bandwidth"/modal dispersion constraints. Actual link distances may be constrained by attenuation, depending on specific loss budget.

Gel-Free Non-Armored OSP Loose Tube (LE Series Gel-Free SJ)

Mechanical Data

AFL NO.	FIBER COUNT	NO. OF TUBES FIBERS/ TUBE	NOMINAL DIAMETER INCHES (MM)	NOMINAL WEIGHT LBS/1,000FT (KG/KM)	MAXIMUM TENSILE LOAD		MINIMUM BEND RADIUS	
					LBS (N)		INCHES (CM)	
					SHORT TERM	LONG TERM	SHORT TERM	LONG TERM
LE012★C5101N1D	12	1/12 (4 fillers)	0.39 (9.8)	49 (73)	600 (2670)	180 (800)	7.8 (20)	3.9 (10)
LE024★C5101N1D	24	2/12 (3 fillers)	0.39 (9.8)	49 (72)	600 (2670)	180 (800)	7.8 (20)	3.9 (10)
LE036★C5101N1D	36	3/12 (2 fillers)	0.39 (9.8)	48 (72)	600 (2670)	180 (800)	7.8 (20)	3.9 (10)
LE048★C5101N1D	48	4/12 (1 filler)	0.39 (9.8)	48 (71)	600 (2670)	180 (800)	7.8 (20)	3.9 (10)
LE060★C5101N1D	60	5/12 (no fillers)	0.39 (9.8)	48 (71)	600 (2670)	180 (800)	7.8 (20)	3.9 (10)
LE072★C6101N1D	72	6/12 (no fillers)	0.42 (10.6)	55 (82)	600 (2670)	180 (800)	8.4 (21)	4.2 (11)
LE096★C8101N1D	96	8/12 (no fillers)	0.48 (12.3)	75 (118)	600 (2670)	180 (800)	9.6 (25)	4.8 (12)
LE144★CC101N1D	144	12/12 (no fillers)	0.62 (15.8)	119 (178)	600 (2670)	180 (800)	12.4 (32)	6.2 (16)
LE216★CI301N1D	216	18/12 (no fillers)	0.62 (15.8)	110 (163)	600 (2670)	180 (800)	12.4 (32)	6.2 (16)
LE288★CO301N1D	288	24/12 (no fillers)	0.75 (19.1)	148 (220)	600 (2670)	180 (800)	15.0 (38)	7.5 (19)

Note: Diameter and weight subject to change without notice

★ Fiber Types – Replace asterisk (★) in AFL number with number in the Fiber Specifications table on previous page.

Reel Information

ITEM	REEL A		REEL B		REEL C		REEL D		REEL E	
	INCHES	CM	INCHES	CM	INCHES	CM	INCHES	CM	INCHES	CM
Reel Height	42	106.7	58	147.3	66	167.6	72	182.8	84	213.4
Reel Width Outside	36	91.4	38	96.5	42	106.7	42	106.7	40	101.6
Reel Width Inside	32	81.6	32	81.3	36	91.4	36	91.4	34	86.4
Drum Diameter	23	58.7	28	71.1	36	91.4	36	91.4	35	88.9
Arbor Hole Diameter	3	7.9	3	7.9	3	7.9	3	7.9	3	7.9
Reel Weight With Lagging	180 lbs	82 kg	420 lbs	191 kg	685 lbs	311 kg	710 lbs	320 kg	950 lbs	431 kg

AFL typically provides Loose Tube cable on several standard sizes of non-returnable wooden reels. Non-standard reel sizes are available upon request. Larger reel sizes may be required to accommodate long cable lengths.