

Indoor/Outdoor Multi-unit Plenum Tight Buffered Cable

AFL now offers high fiber count Indoor/Outdoor Plenum Cables. Designs are based on water-blocked 12-fiber sub-units that are helically stranded to provide sub-unitized cables ranging from 36 to 72 fiber counts. These cables are OFNP listed for indoor and indoor/outdoor applications. Both the sub-unit jackets and outer sheath contain a UV stabilizer and anti-fungus protection for use in outdoor applications. Sub-units contain a water-swellable aramid and 12 tight buffered fibers.


Features

- Available with 36 to 72 fibers
- 12-fiber water-blocked sub-units
- Moisture-resistant, fungus-resistant and UV-resistant outer jacket

Applications

- ONFP inside plant and outside plant environments

Cable Components



Fiber Specifications

CORE SIZE/FIBER TYPE	ISO/IEC	MAXIMUM ATTENUATION (DB/KM)			OVERFILL LAUNCH MIN. BANDWIDTH (MHZ•KM)		EMB _c (MHZ•KM)	GIGABIT ETHERNET MIN. LINK DISTANCE (METERS)		10 GIGABIT ETHERNET MIN. LINK DISTANCE (METERS)	
		850 NM	1300 NM	1550 NM	850 NM	1300 NM		850 NM	1300 NM	850 NM	1300 NM
(6) 62.5 Giga-Link™ 300	OM1	3.5	1.2	N/A	200	600	N/A	300	550	32	—
(5) 50 Giga-Link™ 600	OM2	3.5	1.5	N/A	500	500	N/A	600	600	82	—
(L) 50 Laser-Link 300	OM3	3	1.2	N/A	1,500	500	2,000	1,000	550	300	—
(C) 50 Laser-Link 550	OM4	3	1.2	N/A	3,500	500	4,700	1,040	550	550	—
(W) AFL Wideband Multimode	OM5	3	1.2	N/A	3,500	500	4,700	1,040	550	550	—
(9) Single-mode (ITU G.652.D/G.657.A1)	OS2	N/A	0.5	0.5	N/A	N/A	N/A	N/A	5,000	N/A	10,000



Indoor/Outdoor Multi-unit Plenum Tight Buffered Cable

Mechanical Data

CABLE TYPE	AFL NO.	FIBER COUNT	NOMINAL DIAMETER	WEIGHT	TENSION		BENDING RADIUS	
	PLENUM		INCHES (MM)	LBS/1000 FT (KG/KM)	LBS (N)		INCHES (CM)	
					INSTALLATION	LONG TERM	INSTALLATION	LONG TERM
Indoor/Outdoor Tight Buffered Cable	KQ036★591##1	36	0.62 (15.7)	155 (225)	300 (1320)	90 (396)	9.3 (23.6)	6.2 (15.7)
	KQ048★591##1	48	0.68 (17.2)	190 (280)	300 (1320)	90 (396)	10.2 (25.8)	6.8 (17.2)
	KQ060★591##1	60	0.75 (19.0)	240 (350)	300 (1320)	90 (396)	11.3 (28.5)	7.5 (19.0)
	KQ072★591##1	72	0.82 (20.8)	290 (430)	300 (1320)	90 (396)	12.3 (31.2)	8.2 (20.8)

★ Fiber Types – Replace asterisk (★) in AFL number with number in the Fiber Specifications table on previous page.
 # Outer Jacket Color – Replace hashtag (#) in AFL number with number in the Cable Jacket Color table below.

Cable Jacket Color Options

1 - Blue	8 - Black
2 - Orange	9 - Yellow
3 - Green	A - Violet
4 - Brown	B - Rose
5 - Slate	C - Aqua
6 - White	K - Erika Violet (RAL 4003)
7 - Red	

Qualifications

GOVERNING BODY	STANDARD CODE	COMPONENT
Telcordia	GR-20-CORE	Water-Blocked Cabled Buffer Tube Core
EIA/TIA	598-A/GR-409-CORE	Sub-units
ICEA	S-104-696	Sub-units
RoHS	2002/95/EC	Cable

Temperature Specifications

TEMPERATURE RANGE	
Installation	-20°C to +75°C
Operation	-40°C to +75°C
Storage	-40°C to +75°C

Contact AFL for further details.