





Features

- Less than 20" overall length; ideal for small hand-holes
- Optimized for AFL WTC but also supports stranded loose tube or ribbon fiber cables in either armored or dielectric configurations
- Installation and re-entry requires only a common can wrench
- Fully sealed to protect fiber and splices ensuring longevity
- Kitted with all parts to install up to two WTC cables (strength member retention not included - not required for WTC)
- Designed and tested to Telcordia® GR-771 requirements

LightGuard® 350-20-WTC Sealed Fiber Optic Splice Closure

The LightGuard (LG) 350-20-WTC is a sealed dome closure designed for medium count fiber splicing (up to 144 single or 576 mass) in a butt configuration where space may be limited. The LG-350-20-WTC has been designed and optimized for use in conjunction with AFL Wrapping Tube Cable (WTC), with SpiderWeb® Ribbon (SWR). The WTC-focused design provides a basket for easy slack management. Additionally, WTC SpiderWeb Ribbon bundles can be routed and secured to splice trays without the use of transition tubing (when using AFL's WTC-SWR Bundle Splice Tray Retention Kit), greatly reducing installation time. Transition tubing kits are also available if desired.

Specifications

PARAMETER	VALUE		
Splice Capacity (Max.)—Single, Mass, Mechanical	144, 576, 48		
Number of Splice Trays (Max.) - Single , Mass, Mechanical*	4, 4, 4		
Cable Entrance Configuration	Butt		
Cables	2 to 8 Express with up to 12 Drop		
Cable Sizes (Min. O.D Max. O.D.) Included Grommets Single in. (mm)	(2) Express Ports 0.40" - 1.00" (10.0 - 25.4)	(3) Drop Ports 0.26" - 0.80" (6.6 - 20.0) (Drop Port Entry Kits Not Included)	
(4) Flat Drop Only in. (mm)		(4 port) 0.26" - 0.80" (6.6 - 20.0)	
Additional Grommets Dual Express Port Only in. (mm) Quad Express Port Only in. (mm) (4) Flat Drop Port Only in. (mm)	(6.6 - 11.2)	0.19" x 0.34" (4.8 x 8.6) or 0.25" round (6.4)	
Dimensions - (L x D) in. (mm)	19.8" x 10.0" (503.0 x 254.0)		
Weight - lbs. (kg)	12.0 (5.44)		

Ordering Information

DESCRIPTION	MODEL NO.	AFL NO.
LG-350-20-WTC Fiber Optic Splice Closure—Stores 144 single fusion	LG-350-20-WTC-U	FC001348
or 576 mass fusion, includes (2) Express cable kits for sealing/retention		
and (2) ground terminals with removable bond.		
Does not include: Cable grounding kits, hanger brackets, splice trays		
or drop port entry kits		
LL-4808L-R Universal Splice Tray—Stores (36) single fusion splices or (12)	LL-4808L-R	FA000037
mass fusion splices (144 F). Maximum of 4 trays in the LG-350-20-WTC		
LL-4808-R Mass Splice Tray—Stores (12) mass fusion splices (144 F).	LL-4808-R	FA000020
Maximum of 4 trays in the LG-350-20-WTC		
LL-4808-L Single Splice Tray—Stores (36) single fusion splices. Maximum	LL-4808-L	FA000021
of 4 trays in the LG-350-20-WTC		

Telcordia is a registered trademark of Telcordia Technologies, Inc.



LightGuard® 350-20-WTC Sealed Fiber Optic Splice Closure

Ordering Information (cont.)

DESCRIPTION	MODEL NO.	AFL NO.
LG-350 Single Grommet Kit (Min. 0.40" - Max. 1.00")—For use in LG-55/LG-350/LG-350-AC/SD/WTC on Express Port side	LG-350 Exp Single Kit	FC000726
LG-350 Dual Grommet Kit (Min. 0.26" - Max. 0.44")—For use in LG-55/ LG-350/LG-350-AC/SD/WTC on Express Port side	LG-350 Exp Dual Kit	FC000337
LG-350 Quad Grommet Kit (Min. 0.26" - Max. 0.38")—For use in LG-55/ LG-350/LG-350-AC/SD/WTC on Express Port side	LG-350 Exp Quad Kit	FC000421
LG-350 Single Grommet Kit (Min. 0.26" - Max. 0.80")—For use in LG-350/LG-350-AC/SD/WTC on Drop Port side	LG-350 Drop Single Kit	FC000727
LG-350 Drop 4 Flat Drop Grommet Kit—For use with standard flat drop cable and round cable up to 0.25" O.D.	LG-350 Drop 4 Flat Kit	FC000422
Universal Aerial Strand Hanger Kit—For use with LG-150/250/350	Universal Hanger	FC000006
Extended Offset Strand Hanger Kit—For use with LG-150/250/350	Extended Offset Hanger	FC000208
Pole or Wall Mount Bracket—For use with LG-150/250/350	PWK	FC000592
Closure Stand for Sealed Dome Closures (LG-150, LG-250, LG-350, LG-350-AC, LG-350-SD, LG-350XL)	Sealed Closure Stand	FC001176
Cable Grounding Kit (pack of 5)—Clamp-On Ground Cable Only	CGK-5	FC001091
*Mechanical Splice Kit. Includes 10 pieces of VHB tape. Used in all splice trays. Each piece holds 12 splices.	VHB Tape	FA000089
O-Ring and Lock Ring Kit—For use with LG-350/AC/SD/WTC	LG-350 O-Ring Lock Ring Kit	FC000775
Transition Tubing Kit - Includes 25 pieces of 25" long tubes for WTC bundles	Tubing Kit	FC001372
WTC-SWR Bundle Splice Tray Retention Kit - Includes 25 foam grommets for retaining SWR bundles to splice trays	Foam Retention Kit	HW000406

^{*} See Accessory Specifications. See Splice Tray Specifications.