



LightGuard® 350-27-WTC Sealed Fiber Optic Splice Closure

The LightGuard (LG) 350-27-WTC is a sealed dome closure designed for large count fiber splicing (up to 180 single or 864 mass) in a butt configuration. The LG-350-27-WTC has been designed and optimized for use in conjunction with AFL Wrapping Tube Cable (WTC), with SpiderWeb Ribbon® (SWR®). The WTC-focused design provides a dedicated channel for fiber bundle routing as well as a basket for easy slack management. Additionally, WTC SpiderWeb Ribbon bundles may be routed and secured to splice trays without the use of transition tubing, when using AFL's WTC-SWR Bundle Splice Tray Retention Kit, greatly reducing installation time.

Features

- Dedicated SWR Bundle routing channel protects fibers and eliminates the need for time-consuming transition tubes
- Optimized for AFL WTC but also supports stranded loose tube or ribbon fiber cables in either armored or dielectric configurations
- Installation and re-entry requires only a common can wrench
- Fully sealed to protect fiber and splices ensuring longevity
- Kitted with all parts to install up to two WTC cables (strength member retention not included - not required for WTC)
- Designed and tested to Telcordia® GR-771 requirements

Specifications

PARAMETER	VALUE	
Splice Capacity (Max.)—Single, Mass, Mechanical	180, 864, 36	
Number of Splice Trays (Max.) - Single, Mass, Mechanical*	3, 3, 3	
Cable Entrance Configuration	Butt	
Cables	5 to 11	
Cable Sizes (Min. O.D. - Max. O.D.) Included Grommets Single in. (mm)	(2) Express Ports 0.40" - 1.00" (10.0 - 25.4)	(3) Drop Ports 0.26" - 0.80" (6.6 - 20.0) (Drop Port Entry Kits Not Included)
Additional Grommets Dual Express Port Only in. (mm)	0.26" - 0.44" (6.6 - 11.2)	
Quad Express Port Only in. (mm)	0.26" - 0.38" (6.6 - 9.7)	
(4) Flat Drop Port Only in. (mm)		0.19" x 0.34" (4.8 x 8.6) or 0.25" round (6.4)
Dimensions - (L x D) in. (mm)	28.0" x 10.0" (710.0 x 254.0)	
Weight - lbs. (kg)	16 (7.26)	

Ordering Information

DESCRIPTION	MODEL NO.	AFL NO.
LG-350-27-WTC Fiber Optic Splice Closure—Stores 180 single fusion or 864 mass fusion, includes (2) Express cable kits for sealing/retention and (2) ground terminals with removable bond. Does not include: Cable grounding kits, hanger brackets, splice trays or drop port entry kits	LG-350-27-WTC-U	FC001349
LL-7644 Universal Splice Tray—Stores (60) single fusion splices or (24) mass fusion splices (288 F). Maximum of 3 trays in the LG-350-27-WTC	LL-7644	FA000044
LL-7144 Mass Splice Tray—Stores (24) mass fusion splices (288 F). Maximum of 3 trays in the LG-350-27-WTC	LL-7144	FA000043
LL-7060 Single Splice Tray—Stores (60) single fusion splices. Maximum of 3 trays in the LG-350-27-WTC	LL-7060	FA000042

Telcordia is a registered trademark of Telcordia Technologies, Inc.

LightGuard® 350-27-WTC Sealed Fiber Optic Splice Closure

Ordering Information (continued)

DESCRIPTION	MODEL NO.	AFL NO.
LG-350 Single Grommet Kit (Min. 0.40" - Max. 1.00")—For use in LG-55/LG-350/LG-350-AC/SD/WTC on Express Port side	LG-350 Exp Single Kit	FC000726
LG-350 Dual Grommet Kit (Min. 0.26" - Max. 0.44")—For use in LG-55/LG-350/LG-350-AC/SD/WTC on Express Port side	LG-350 Exp Dual Kit	FC000337
LG-350 Quad Grommet Kit (Min. 0.26" - Max. 0.38")—For use in LG-55/LG-350/LG-350-AC/SD/WTC on Express Port side	LG-350 Exp Quad Kit	FC000421
LG-350 Single Grommet Kit (Min. 0.26" - Max. 0.80")—For use in LG-350/LG-350-AC/SD/WTC on Drop Port side	LG-350 Drop Single Kit	FC000727
LG-350 Drop 4 Flat Drop Grommet Kit—For use with standard flat drop cable and round cable up to 0.25" O.D.	LG-350 Drop 4 Flat Kit	FC000422
Universal Aerial Strand Hanger Kit—For use with LG-150/250/350	Universal Hanger	FC000006
Extended Offset Strand Hanger Kit—For use with LG-150/250/350	Extended Offset Hanger	FC000208
Pole or Wall Mount Bracket—For use with LG-150/250/350	PWK	FC000592
Closure Stand for Sealed Dome Closures (LG-150, LG-250, LG-350, LG-350-AC, LG-350-SD, LG-350XL)	Sealed Closure Stand	FC001176
Cable Grounding Kit (pack of 5)—Clamp-On Ground Cable Only	CGK-5	FC001091
*Mechanical Splice Kit. Includes 10 pieces of VHB tape. Used in all splice trays. Each piece holds 12 splices.	VHB Tape	FA000089
O-Ring and Lock Ring Kit—For use with LG-350/AC/SD/WTC	LG-350 O-Ring Lock Ring Kit	FC000775
WTC-SWR Bundle Splice Tray Retention Kit - Includes 25 foam grommets for retaining SWR bundles to splice trays	Foam Retention Kit	HW000406
Strength Member Retention Bracket Kit (10 pieces, for use with stranded loose tube or central tube ribbon cables requiring strength member retention)	Strength Member Kit	FC001362

* See Accessory Specifications.
See Splice Tray Specifications.