



## LightGuard® 600 Aerial Weathertight Fiber Optic Splice Closure

The LightGuard (LG) 600 Aerial Weathertight Fiber Optic Splice Closure is designed for high count fiber splicing (up to 384 single or 1152 mass) in a butt or in-line configuration. Utilized in aerial applications, the LG-600 is an ideal cost-effective solution for high fiber count splicing and requires only a common can wrench for installation.

### Specifications

PARAMETER	VALUE
Splice Capacity (Max.)—Single, Mass, Mechanical	384, 1152, 36
Number of Splice Trays (Max.)—Single, Mass, Mechanical*	12, 8, 8
Cable Entrance Configuration	Butt or In-line
Cables	6 to 24
Cable Sizes (Min. O.D.—Max. O.D.) Included Grommets	<b>(6) Cable Ports</b> 0.44" - 1.00" (11.2 - 25.4)
Single in. (mm)	
<b>Additional Grommets</b>	
Dual Grommet in. (mm)	
6-Port Multi-Drop Grommet in. (mm)	Sm: 0.40" to 0.70" - LG: 0.60" - 0.90" (10.0 - 17.8 / 15.3 - 22.9) 0.30" - 0.48" (7.6 - 17.8)
Dimensions—(L x W x D) in. (mm)	27.0" x 11.3" x 7.5" (690.0 x 286.0 x 190.5)
Weight—lbs. (kg)	18.0 (8.16)

### Features

- Six individual, self-sizing grommeted cable ports (expandable to twelve cable entrances)
- Patented tongue-in-groove cover seal system
- Installation and re-entry only require a common can wrench
- Integrated grounding clamp through aerial hangers
- Cable retention clamps provide pullout rating required by Telcordia®
- Engineered thermoplastic to meet Telcordia® aerial and UV resistance requirements
- Rural Utilities Service (RUS) Listed

### Ordering Information

DESCRIPTION	MODEL NO.	AFL NO.
LG-600 Aerial Weathertight Fiber Optic Splice Closure—Stores 384 single fusion or 1152 mass fusion, includes (4) cable kits for sealing/retention and (2) ground terminals with removable bond and hanger brackets. Not included: Splice Trays or Cable Grounding Kits	LG-600-U-0	FC000029
LL-2400 Single Splice Tray—Stores (24) single fusion splices. Maximum of 12 trays in the LG-600.	LL-2400	91710-06
LL-2448 Universal Splice Tray—Stores (24) single fusion or (4) mass fusion splices (48 F). Maximum of 8 trays in the LG-600, *Mechanical	LL-2448	911289-00-02
LL-4848 Mass Splice Tray—Stores (12) mass fusion splices (144 F). Maximum of 8 trays in the LG-600	LL-4848	911437-00-02
LL-2448-48S Single Splice Tray—Stores (48) single fusion splices. Maximum of 8 trays in the LG-600	LL-2448-48S	FA000045
Large Single Grommet Kit with retention hardware (Min 0.44" - Max 1.00")	Large Single Grommet Kit	FC000623
Large Single Grommet Kit (10 pc grommet only) (Min 0.44" - Max 1.00")	Large Single Grommet Kit (10)	91918-00
Large Dual Grommet Expansion Kit—Includes: (2) Dual grommets and hardware (Min 0.40" - Max 0.70" and Min 0.60" - Max 0.90")	Large Dual Grommet Kit	911406-00-00
Large 6 Port Drop Cable Kit—2 Grommets with retention bracket. Allows six cable entries (Min 0.23" - Max 0.48" and flat drop)	Large 6 Port Drop Kit	FC000352
Adjustable Aerial Hanger Kit Bracket Kit (included with closure)	Adjustable Hanger LG-400/500/600	911497-00-00

continued on next page

Telcordia is a registered trademark of Telcordia Technologies, Inc.

## LightGuard® 600 Aerial Weathertight Fiber Optic Splice Closure (cont.)

### Ordering Information (cont.)

DESCRIPTION	MODEL NO.	AFL NO.
Extended Offset Aerial Hanger Kit LG-400/500/600	Offset Hanger LG-400/500/600	91990-00
SC 6-pack bracket kit for LG-600	Bracket Kit (6-pack SC) LG-600	FM001294
Retention hardware for additional cables or replacement hardware—LG-400/500/600 (no grommets)	Cable Retention Kit LG-400/500/600	FC000356
Closure Extension Kit—Used to join multiple closures for extended sheath openings required to repair cable sheath and damaged fibers	Closure Extension Kit LG-400/500/600	911499-00-00
1x6 Fiber Router Kit with furcation tubes	1x6 Fiber Router	FC000070
Cable Grounding Kit (pack of 5)—Clamp -On Ground Cable Only	CGK-5	FC001091
*Mechanical Splice Kit. Includes 10 pieces of VHB tape. Used in all splice trays. Each piece holds 12 splices.	VHB Tape	FA000089

\* See Accessory and Splice Tray Specifications.