




LL-500 with interconnect kit installed



LL-500 with LL-2450 splice tray installed

LightLink 500 Optical Splicing and Distribution Enclosure

The LightLink (LL) 500 Optic Splicing and Distribution Enclosure provides for organizing, splicing and interconnecting fibers in broadband, distribution and building entrance applications. The enclosure features a scratch and corrosion resistant powder paint coating base and a fully gasketed hinged cover. A unique self-sizing grommet design allows for express and pre-terminated cable installation. The LL-500 supports up to five LL-2450 splice trays for up to 60 single fusion splices or three LL-4850 splice trays (not included in base unit) and an optional 12 fiber, hinged Interconnect Module.

Features

- NEMA 3 rated enclosure
- Independent cable strain relief system
- Cable entry/exit grommet seals
- Fiber routing system
- Splice tray support system
- Hinged cover
- Supports optional Interconnect Modules
- Interconnect Module supports up to 12 SC bulkhead adapters
- Secured with a standard padlock
- 4 cable ports with standard grommets
- 8 cable ports with optional expansion kits

Specifications

PARAMETER	VALUE
Material	Steel
Coatings	Electrostatically applied, powder coat
Color	Antique white
Cable Ports	4-8
Cable Sizes (Max. O.D. – Min. O.D.)	4 @ 0.3-0.77" Up to 8 with Dual Grommet Kits 4 @ 0.3-0.65" 4 @ 0.3-0.5"
Dimensions (H x W x D) in. (cm)	17.5 x 9.0 x 4.0 (44.45 x 22.86 x 10.16)
Weight lbs. (kg)	6.5 (2.95)

Ordering Information

DESCRIPTION	AFL NO.
LL-500-U-0	FM000326
LL-500 Interconnect Kit with SC UPC adapters	FM000385
LL-500 Interconnect Kit with SC APC adapters	FM000407
LL-500 Interconnect Kit without adapters	FM000408
LL-500 with Multi-port Grommets	FM000659
LL-2450 Single Fusion Splice Tray (stores 12 single fusion splices)	91957-00
LL-4850 Mass Fusion Splice Tray (stores 8 mass fusion sleeves - 96 fibers)	91958-00
LL-500 Multi-port Grommet Kit, 6 drop cable entry up to 0.37" OD	FC000573