



MPO Cable Assemblies

MPO cable assemblies provide a high performance plug-and-play solution for premise installations where space is a premium. Used to interconnect panels or cassettes, the small diameter MicroCore® cable construction reduces the required pathway space and provides a flexible outer jacket in both single-mode and multimode configurations. Multiple breakout options are also available including LC, SC, ST, or FC single fiber connectors.

Specifications

PARAMETER	SINGLE-MODE ASSEMBLIES					MULTIMODE ASSEMBLIES		
	LC		SC		MPO	LC	SC	MPO (LOW LOSS)
	ULTRA	ANGLED	ULTRA	ANGLED	ANGLED			
Insertion Loss (Typical dB)***	0.15	0.15	0.15	0.15	0.35	0.15	0.15	0.15
Insertion Loss (Maximum dB)	0.3	0.3	0.3	0.3	0.75	0.5	0.5	0.2
Return Loss (Typical dB)***	-60	-70	-60	-70	-65	-35	-35	-30
Return Loss (Minimum dB)	-55	-65	-55	-65	-55	-30	-30	-20
Temperature Range (°C)	-40 to +85	-40 to +85	-40 to +85	-40 to +85	-40 to +75	-40 to +85	-40 to +85	-40 to +75
Durability Cycles	500	500	500	500	200	500	500	200

*** Typical values based on equal quality connectors.

Features

- High density plug and play fiber optic interconnects
- Pre-terminated cable assemblies eliminate field termination time and guarantee optical performance
- Available with a wide variety of cable and connector options
- Standard and low loss connectors
- Single-mode and laser-optimized multimode fiber available
- Pulling eye option available upon request
- Cable tested to meet or exceed EIA/TIA 568-A/GR-409-CORE
- Telcordia® GR-326/GR-1435 compliant connectors

Applications

- Data center systems wiring
- MPO-MPO or MPO-Fanouts
- Head-end termination to a fiber "backbone"
- Termination of fiber rack systems
- Multi-floor deployment
- Intrabuilding "backbones"

Ordering Information—MPO-MPO Assemblies

(Female MPOs on both ends – no pins)

(Polarity: Key Up/Key Up, Straight Through)

FIBER COUNT	FIBER	PULLING EYE	AFL NO.
12	Single-mode	No	CS009980-XXXX
12	Single-mode	Yes	CS009981-XXXX
24	Single-mode	No	CS009984-XXXX
24	Single-mode	Yes	CS009985-XXXX
72	Single-mode	No	CS009996-XXXX
72	Single-mode	Yes	CS009997-XXXX
12	50 µm 10gig 300 (OM3)	No	CS010649-XXXX
12	50 µm 10gig 300 (OM3)	Yes	CS010650-XXXX
24	50 µm 10gig 300 (OM3)	No	CS003700-XXXX
24	50 µm 10gig 300 (OM3)	Yes	CS009912-XXXX
72	50 µm 10gig 300 (OM3)	No	CS003720-XXXX
72	50 µm 10gig 300 (OM3)	Yes	CS010016-XXXX
12	50 µm 10gig 550 (OM4)	No	CS008420-XXXX
12	50 µm 10gig 550 (OM4)	Yes	CS010165-XXXX
24	50 µm 10gig 550 (OM4)	No	CS010100-XXXX
24	50 µm 10gig 550 (OM4)	Yes	CS010066-XXXX
72	50 µm 10gig 550 (OM4)	No	CS010101-XXXX
72	50 µm 10gig 550 (OM4)	Yes	CS010067-XXXX

NOTE: XXXX is length in meters.

Contact AFL Customer Service for additional polarity schemes available.

continued on next page

MPO Fanout Cable Assemblies



Ordering Information—MPO Fanout Assemblies (Male MPOs — Duplex Connectors)

FIBER COUNT	FIBER	PULLING EYE	AFL NO.	
			MALE MPO-LC DUPLEX	MALE MPO-SC DUPLEX
12	Single-mode	No	CS009521-XXXX	CS010020-XXXX
12	Single-mode	Yes	CS0010017-XXXX	CS010021-XXXX
24	Single-mode	No	CS003796-XXXX	CS010022-XXXX
24	Single-mode	Yes	CS010018-XXXX	CS010023-XXXX
72	Single-mode	No	CS003811-XXXX	CS010024-XXXX
72	Single-mode	Yes	CS010019-XXXX	CS010025-XXXX
12	50 μm 10gig 300 (OM3)	No	CS011510-XXXX	CS010030-XXXX
12	50 μm 10gig 300 (OM3)	Yes	CS010027-XXXX	CS010031-XXXX
24	50 μm 10gig 300 (OM3)	No	CS003795-XXXX	CS010032-XXXX
24	50 μm 10gig 300 (OM3)	Yes	CS010028-XXXX	CS010033-XXXX
72	50 μm 10gig 300 (OM3)	No	CS003810-XXXX	CS010034-XXXX
72	50 μm 10gig 300 (OM3)	Yes	CS010029-XXXX	CS010035-XXXX
12	50 μm 10gig 550 (OM4)	No	CS009519-XXXX	CS010073-XXXX
12	50 μm 10gig 550 (OM4)	Yes	CS010068-XXXX	CS010074-XXXX
24	50 μm 10gig 550 (OM4)	No	CS010069-XXXX	CS010075-XXXX
24	50 μm 10gig 550 (OM4)	Yes	CS010070-XXXX	CS010076-XXXX
72	50 μm 10gig 550 (OM4)	No	CS010071-XXXX	CS010077-XXXX
72	50 μm 10gig 550 (OM4)	Yes	CS010072-XXXX	CS010078-XXXX