



OptiNID® 760XL Optical Demarcation Closure

The OptiNID (OPN) 760XL is an optical demarcation closure designed for use in either indoor or outdoor environments. It is capable of housing up to 24 bulkhead adapters in two 118 LGX® compatible adapter plates and is equipped with a splice tray (LL-2425), which holds up to 24 single fusion splices. The OPN-760XL can be either wall or pole-mounted.



Features

- Capacity for up to two 118 LGX compatible adapter plates
- Rugged weather-resistant thermoplastic alloy
- Self-latching, hinged cover design allows easy access without loose parts
- Slip-in grommets allow pre-connectorized cable deployment
- Provider override is provided so that technician can override customer lock
- Security cover option available



OPN-760XL with optional security cover kit



OPN-760XL with 3/4" Pipe Fitting Transition Kit



3/4" Pipe Fitting Transition Kit

Specifications

PARAMETER	VALUES
Dielectric Strength	Minimum 2500 Vrms for 1 minute
High Temperature Storage/Mold Stress °F (°C)	14 days at 159 (70.55)
Temperature Cycling with Humidity °F (°C)	150 day cycling from 40-140 (4.44-60) with 95% RH
Impact Test °F (°C)	-40 (-40), 5*/lbs on all external surfaces
Drop Test °F (°C)	-40 (-40), 5* (12.7 cm) onto concrete surface 4 times
Rain	24 hours at 10 psi
UV Resistance (Days Exposed)	60 per ASTM-G26-84
Salt Fog (Days Exposed)	60 per ASTM-BLL7-90
Flammability	UL94-5V
Chemical Resistance 30 Days at 100 °F and 95% RH Subject to:	Resists chipping and/or cracking when subject to: house paint, wasp spray, sulfuric acid, kerosene and sodium hydroxide
Material	UL® listed flame retardant thermoplastic alloy
Dimensions (H x W x D) in. (cm)	13 x 13 x 3.75 (32.5 x 32.5 x 9.5)
Cable Entrances in. (cm) diameter—Input	4 x 0.875 (2.2)—3/4" conduit
Covers	Standard – molded-in snap finger and 3/8" hex head fastener

Ordering Information

DESCRIPTION	AFL NO.
BASE PRODUCT ^{1,2}	
OptiNID OPN-760XL, No Adapters, No Security Cover	DM001000
OptiNID OPN-760XL, No Adapters, Security Cover	DM001022
ACCESSORIES ³	
3/4" Pipe Fitting Transition Kit (includes 2)	DM001174
OPN-760XL Security Cover Kit	DM000923
OPN-760XL Pole Mounting Kit	DM000927

Notes:

1. All standard OPN-760XL configurations come equipped with four slip-in rubber grommets and a splice tray equipped for 32 single fusion splices.
2. Contact AFL customer service for additional configurations.
3. See OptiNID Accessory Page for additional kits.

LGX is a registered trademark of Furukawa Electric North America, Inc.